

# Purolite® A600E/9149

Polystyrenic Gel, Type I Strong  
Base Anion Resin, Chloride form,  
Potable Water Grade

## PRINCIPAL APPLICATIONS

- Hexavalent chromium ions removal
- Nitrate Removal
- Uranium Removal
- Sulfate Removal

## ADVANTAGES

- High operating capacity
- Exceptional physical stability
- Good kinetic performance

## REGULATORY APPROVALS

- Compliant with FDA Regulation 21 CFR 173.25 for Food Treatment, Ion Exchangers
- Certified by the WQA to NSF/ANSI-61 Standard
- Water Regulations Advisory Scheme Approved

## TYPICAL PACKAGING

- 1 ft<sup>3</sup> Sack
- 25 L Sack
- 5 ft<sup>3</sup> Drum (Fiber)
- 1 m<sup>3</sup> Supersack
- 42 ft<sup>3</sup> Supersack

## TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Gel polystyrene crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Type I Quaternary Ammonium
Ionic Form	Cl <sup>-</sup> form
Total Capacity	1.6 eq/L (35.0 Kgr/ft <sup>3</sup> ) (Cl <sup>-</sup> form)
Moisture Retention	42 - 45 % (Cl <sup>-</sup> form)
Mean Diameter	570 ± 50 µm
< 425 µm (max.)	1 %
Uniformity Coefficient (max.)	1.2
Specific Gravity	1.09
Shipping Weight (approx.)	675 - 710 g/L (42.2 - 44.4 lb/ft <sup>3</sup> )
Temperature Limit	100 °C (212.0 °F) (Cl <sup>-</sup> form)
Temperature Limit	60 °C (140.0 °F) (OH <sup>-</sup> form)



**Americas**  
T +1 610 668 9090  
F +1 610 668 8139  
americas@purolite.com

**Europe**  
T +44 1443 229334  
F +44 1443 227073  
europe@purolite.com

**Asia Pacific**  
T +86 571 876 31382  
F +86 571 876 31385  
asiapacific@purolite.com